

All fires, fast

firexo

FIREXO 9LTR EXTINGUISHER

Model/Product Number 809-765-347-906

Name	Firexo 9LTR extinguisher
Model/Product number	809-765-347-906
Capacity (litres)	9
Cylinder Height (mm)	580
Outer Diameter (mm)	583
Cylinder Material	Steel
Pressurizing Gas	Nitrogen
Test Pressure (bar)	30 bar
Working Pressure at 20 °C	12 bar
Weight Full (kg)	15.79
Weight Empty (kg)	4.9
Spray Range (m)	1 – 4
Discharge Time at 20 °C (seconds)	45 – 55
Temperature Range (°C)	minus 12 / plus 60
Warranty	5yr
Fire Rating	55A/113B/C/D/E/75F
CE Approval	CE 0036



ALL FIRES.



METHOD OF USE

Discharge entire contents onto the fire from 1 to 3 metre distance. This extinguisher should be serviced at least once a year by an approved Firexo service engineer only in accordance with BS5306. Recharging should be carried out to BS 5306-9:2015 only using recommended by the manufacturer. Tested on electrical to 35 kV.

Call **0207 989 6101**

© FIREXO 2019

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.

firexo

firexo.com

All fires, fast

firexo

FIREXO 6LTR EXTINGUISHER

Model/Product Number 809-765-347-876

Name	Firexo 6LTR extinguisher
Model/Product number	809-765-347-876
Capacity (litres)	6
Cylinder Height (mm)	497
Outer Diameter (mm)	510
Cylinder Material	Steel
Pressurizing Gas	Nitrogen
Test Pressure (bar)	30 bar
Working Pressure at 20 °C	12 bar
Weight Full (kg)	10.76
Weight Empty (kg)	3.5
Spray Range (m)	1 – 4
Discharge Time at 20 °C (seconds)	30 – 40
Temperature Range (°C)	minus 12 / plus 60
Warranty	5yr
Fire Rating	34A/113B/C/D/E/75F
CE Approval	CE 0036



ALL FIRES.



METHOD OF USE

Discharge entire contents onto the fire from 1 to 3 metre distance. This extinguisher should be serviced at least once a year by an approved Firexo service engineer only in accordance with BS5306. Recharging should be carried out to BS 5306-9:2015 only using recommended by the manufacturer. Tested on electrical to 35 kV.

Call **0207 989 6101**

© FIREXO 2019

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.

firexo

firexo.com

All fires, fast

firexo

FIREXO 2LTR EXTINGUISHER

Model/Product Number 809-765-347-846

Name	Firexo 2LTR extinguisher
Model/Product number	809-765-347-846
Capacity (litres)	2
Cylinder Height (mm)	405
Outer Diameter (mm)	340
Cylinder Material	Steel
Pressurizing Gas	Nitrogen
Test Pressure (bar)	30 bar
Working Pressure at 20 °C	12 bar
Weight Full (kg)	3.82
Weight Empty (kg)	1.4
Spray Range (m)	1 – 3
Discharge Time at 20 °C (seconds)	20 – 30
Temperature Range (°C)	minus 12 / plus 60
Warranty	5yr
Fire Rating	13A/34B/C/D/E/25F
CE Approval	CE 0036



ALL FIRES.



METHOD OF USE

Discharge entire contents onto the fire from 1 to 3 metre distance. This extinguisher should be serviced at least once a year by an approved Firexo service engineer only in accordance with BS5306. Recharging should be carried out to BS 5306-9:2015 only using recommended by the manufacturer. Tested on electrical to 35 kV.

Call **0207 989 6101**

© FIREXO 2019

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.

firexo

firexo.com